

Solenoid metering pump CONCEPT^{PLUS} 240 strokes/min

ProMinent®



The necessary retrofitting can be carried out at the customer's premises with a specially designed external control retrofit kit. This reduces storage costs without limiting flexibility.

The product range CONCEPT^{PLUS} covers the performance range from 0.74 l/h-10 bar to 14.9 l/h-1.5 bar. With its compact structure it is equally suitable for both conventional installation on a bracket or chemical tank and installation in machines such as slide grinding systems, car wash systems and dish-washers.

The metered quantity can be steplessly adjusted by means of the stroke length over a range of 10 % - 100 % and in four levels by means of the stroke rate. This results in an adjustment range of 1:40. As well as manual stroke rate adjustment the pump can be controlled by potential-free contacts from a water meter or controller. The pump can also be activated and deactivated with a potential-free contact.

A 'level' retrofit kit is available for connecting a level switch. The dosing heads are available in the material combinations PPE 2, PVT 2 and NPB 2 with bleed valve to cover virtually all metering tasks in water treatment.

CONCEPT^{PLUS} offers uncompromising quality and reliability at an extremely affordable price.

Solenoid metering pump CONCEPT^{PLUS} 240 strokes/min

Type	Type Pump capacity at max. back pressure			Pump capacity at medium back pressure			Stroke rate Strokes/min.	Connection size outØ x inØ mm	Suction lift* mWs	Shipping weight approx. kg
	bar	l/h	ml/stroke	bar	l/h	ml/stroke				
CNPb 1001	10	1.0	0.07	5	0.97	0.09	240	6x4	6	1.8
CNPb 1602	16	1.5	0.10	8	1.9	0.13	240	6x4	6	1.8
CNPb 1003	10	3.0	0.21	5	4.3	0.24	240	6x4	5	1.8
CNPb 0705	7	5.2	0.36	3,5	5.87	0.59	240	6x4	4	1.8
CNPb 0312	3	12.0	0.83	1,5	17.3	1.00	240	8x5	2	1.8
CNPb 0223	1.5	21.9	1.52	1	25.2	1.63	240	8x5	1.5	1.8

* Suction lift with a filled dosing head and suction line
Electrical connection: 100 V -230 V, 50/60 Hz
The system includes: 2 m mains cable with standard European plug, foot valve, injection valve, 2 m suction line and 5 m discharge line

Optional: External control retrofit kit 2 m control cable and level retrofit kit for connecting a one-stage level switch

Order no. 1046731



Wetted materials in different versions

Liquid end	Dosing head	Suction/pressure connector	Valve ball	Seals
PPE	Polypropylene	Polypropylene	Ceramic	EPDM
NPB	Acrylic	PVC	Ceramic	FPM B
PVT	PVDF	PVDF	Ceramic	PTFE

* DEVELOPAN® diaphragms with PTFE support in all versions

Addresses and delivery information from the Distributor:
ProMinent Fluid Controls (Thailand) Co.,Ltd
2991/7 Ladprao Road,
Klongchang, Bangkok,
Bangkok 10240 THAILAND
Tel. +662-3760008, 3701610
Fax. +662-3760013, 3760130
E-mail: pfc@prominent.co.th
Website: www.prominent.co.th